

DESCRIPTION

Solenoid valve 3 way normally closed in stainless steel AISI 316 direct acting poppet type.

With explosion proof coil certified for hazardous area:

ATEX II 2GDEx d IIC T6 o T5 o T4 Gb

Ex tb IIIC T80°C o T95°C o T130°C Db IP66

Tamb -40°C ÷ +35°C(T6) o +50°C(T5) o +60°C(T4)

(other certifications e.g.. EAC, INMETRO, CCOE etc. on request)



3

VALVE CONSTRUCTION

Body	AISI 316
Armature tube	AISI 316
Plunger and core	AISI 430FR
Springs	AISI 316
Seal material	FPM

EXPLOSION PROOF COIL CONSTRUCTION

Housing	Red colour alloy (painted with epoxy powder)
Electrical connection	1/2" NPT (M20x1 on request)



FEATURES

Maximum allowable pressure PS 80bar^③

Maximum fluid viscosity 25cSt (mm²/s)

Ambient temperature: -40°C ÷ +35°C(T6), +50°C(T5), +60°C(T4)

Mounting position with vertical coil above



NOTE: The solenoid valve is suitable only with media that are **NOT** potentially explosive

CODE ① ②	Connection G ISO 228	Orifice mm		Kv m ³ /h	Differential pressure bar			Nominal power		Coil Series	Seal ①	Temp. range °C
		1→2	2→3		Min	Max		AC Holding	DC			
A370B...15///...	1/4"	1.5	2.4	0.07	0	16	16	12 VA	8W	A6	NBR=B EPDM=E FPM=V	-10 +80
A370B...20///...		2	2.4	0.11	0	13	13					
A370B...25///...		2.5	2.4	0.16	0	10	10					

① Seal

Example: A370BV15///A6B FPM seal


Coil 24V 50/60Hz

② Coil

③ REMARK

The maximum allowable pressure PS for steam 2,5bar (gauge pressure)

COIL ②	Alternating Current 50/60Hz (V)				Direct Current (V)			Electrical connection	DESCRIPTION Voltage tolerance AC +15% -10% DC ± 10% Protection class IP66 Continuous service ED100%
	24	48	110	220 230	12	24	48		
Series A6	A6B	A6C	A6D	A6E	A60	A61	A62	1/2" NPT	


OVERALL DIMENSION
