



KP-01

GALAXY CAPACITIVE LEVEL ELECTRODE

GENERAL FEATURES

Ayvaz KP-01 Capacitive Level Controller works according to capacitance measurement principle. It is used to display continuous levels in conductive and non-conductive liquids. KP-01 comprises a level transmitter which is integrated into the electrode that produces a standard analog signal of 4-20mA. Analog output of 4-20mA can be monitored from the display located on the panel protection box. KP-01's display both 4-20mA analog output and liquid level as percentage in tank or the boiler. A specially designed and winglet-fit cooling pipe is used for heat insulation of the electrode.

Capacitance measurement principle is used to indicate the level. Electrode rod and vessel wall form a capacitor. It is basically based on the fact that the value of a capacity is affected by dielectric value of the substance between the plates and from the plate areas, as well as from the distance between them. As the area of the electrode and tank wall is fixed, the only variable thing is the substance inside the tank which plays a dielectric role.

If the level of such dielectric substance changes, the current running through the plates would change proportionately, as well. A dielectric is defined as an insulating substance which keeps many liquids such as water outside.

Dielectric constant of air and vacuum is 1 while it is bigger than 1 for other substances and therefore, capacity changes in line with the change in amount of the substance inside the tank. In order to obtain a useful result of measurement, measuring rod (dip stick) dipped at various depths into liquids must be insulated entirely. After zero point measuring range is adjusted, level can be read through the display unit.

Application Areas


- Steam Boilers
- Supply Tanks
- Concrete Tank
- Plastic Tanks
- Chemical Industry
- Food Industry
- Marine
- Pharmaceutical Industry

PRODUCT FEATURES	
Body	AISI 316 Ti
Elec. Box	Aluminium
Flange	Forged Steel
Electrode	AISI 316 Ti
Electrode Insulation	PTFE
Connection	3/4" BSP / DN32-50 PN40 Flanged
Intermediate Disc	PTFE
Max. Working Temp.	238°C
Max. Working Pressure	32 Bar
Thermal Fuse	115°C
Supply	230 V (Opt. 115V, 24V)+ %10, 50-60 Hz
Power Consumption	5 VA
Precision	Degree 1: Water > 0.5 µS
	Degree 2: Water > 0.20 Ms
	Degree 3: Fuel oil or 2,3
Output	4-20 mA Analog and Proportional
Protection Class	IP44


KP-01 GALAXY CAPACITIVE LEVEL ELECTRODE

Working Principle:

To define electrical capacity, we assume that two conductive plates are used:



Due to leakage currents and the distance (d) between tank and probe is relatively high, above equation is not practical to use. Therefore, instead of electrical capacity, impedance measurement will provide accurate level results.



Impedance is $Z = R + jL\omega + (jC\omega)^{-1}$. R is defined as real component and represents the medium conductivity.

$jL\omega$ is the second component and defined as inductive reactance. This component is ignored. Hence, the chance of extra error due to electrostatic measuring is removed. Final impedance formula becomes as follow $Z = R + (jC\omega)^{-1}$. The capacitive level measurement we manufacture works on the transfer of electrical charges principle.

Total impedance is defined as $Z = V / I$.

I (Current) $I = Q / t$

Q (Coulomb)

t (sn)

$(jC\omega)^{-1}$ is the capacitive reactance we want to measure. So, electrical charges and impedance are on the same phases. In brief, electrical charges flowed into medium are directly proportional with capacitive reactance.

For coaxial sensor;

a = Radius of electrode

b = Radius of insulated electrode


L = Length

Impedance can be defined as follows:
$$\frac{2\pi\epsilon_0\epsilon_r}{\ln(b/a)} \cdot L$$

Excitation applied between 10KHz.250KHz based on length for all our models. $\omega = 2\pi f$ Linearity error that may be caused by conductivity component (R) effect is prevented by electronic circuit design and mechanical design. Reduced to a level lower than 1ppm, acceptable as zero.

KP-01 GALAXY CAPACITIVE LEVEL ELECTRODE

TECHNICAL SPECIFICATION - THREADED




L (mm)	L1 (mm)
300	373
400	477
500	583
600	688
700	794
800	899
900	1004
1000	1110
1100	1214
1200	1319
1300	1423
1400	1528
1500	1636
2000	2156

Part No / Name	Material
1 Cover	Aluminium
2 Board Body	Aluminium
3 Control Board Circuit	Stripboard
4 Board Connection Bolt	8.8
5 Bolt Gasket	Lastik
6 Heat Insulation Pipe Cover	Castermid
7 Heat Insulation Pipe	Aluminium
8 Rivet	
9 Heat Insulation Pipe Connec.	Castermid
10 A.K.B. Nut	
11 Washer	
12 Electrode Fixing Bolt	AISI 316
13 Electrode Fixing	Peek
14 Spring Pressure Bear	AISI 304
15 Electrode Pressure Spring	AISI 302
16 Electrode Body	AISI 316Ti
17 Electrode Body Gasket	AISI 304
18 Fixing Part	AISI 316
19 Rivet	Ø2x4
20 PFA Insulation	PFA
21 Electrode Pipe	AISI 316Ti
22 Wire Cover	Teflon
23 Wire	Weld Wire
24 Stopper	PFA
25 Board Cover Gasket	Silicon
26 Raccord	
27 Raccord	
28 Washer	
29 Cylindrical Head Bolt	
30 Gasket	
31 Countersunk Bolt	

KP-01 GALAXY CAPACITIVE LEVEL ELECTRODE

TECHNICAL SPECIFICATION - FLANGED




L (mm)	L1 (mm)
275	316
375	420
475	526
575	631
675	737
775	842
875	947
975	1053
1075	1157
1175	1262
1275	1366
1375	1471
1475	1579
1975	2099


Part No / Name	Material
1 Cover	Aluminium
2 Board Body	Aluminium
3 Control Panel Circuit	Stripboard
4 Panel Connector Bolt	8.8
5 Pano Bağlantı Civata Contası	Lastik
6 Isı Yalıtım Borusu Kapağı	Castermid
7 Heat Isolation Pipe	Alüminyum
8 Perçin	
9 Isı Yalıtım Borusu Ara Parça	Castermid
10 A.K.B. Nut	
11 Washer	
12 Elektrod Sabitleme Cıvatası	AISI 316
13 Elektrod Sezgi Sabitleyicisi	Peek
14 Yay Baskı Yatağı	AISI 304
15 Elektrod Baskı Yayı	AISI 302
16 Elektrod Gövdesi	AISI 316Ti
17 Elektrod Gövde Contası	AISI 304
18 Sabitleme Parçası	AISI 316
19 FLANŞ DN50 PN40	C 22,8
20 Perçin	
21 Perçin	
22 Muhabaza Borusu	AISI 304
23 PFA Kılıf	PFA
24 Elektrod Sezgi Çubuğu	AISI 316Ti
25 Tel kılıfı	Teflon
26 Wire	Weld Wire
27 Tapa	PFA
28 Perçin	
29 Merkezleme Parçası	PFA
30 Pano Kapak Contası	Silicon
31 Raccord	
32 Raccord	
33 Washer	
34 Silindirik Başlı Cıvata	
35 Gasket	
36 Havşa Başlı Civata	

KP-01 GALAXY CAPACITIVE LEVEL ELECTRODE

3D APPLICATION SAMPLE



Electrical Connection Scheme



For electrical connection, minimum 1.5 mm² multi-core cable should be used.



KP-01 GALAXY CAPACITIVE LEVEL ELECTRODE

KP-01

GALAXY CAPACITIVE LEVEL ELECTRODE



HEAD OFFICE - FACTORY

Atatürk Sanayi Bölgesi Hadimköy Mahallesi Mustafa İnan Caddesi No: 44 Arnavutköy - İSTANBUL
Tel: +90 212 771 01 45 (pbx) | Fax: +90 212 771 47 27
info@ayvaz.com | www.ayvaz.com

**Cona
Caserta/Italy**
Tel: +39 0823 187 3988
rmolaro@ayvaz.com

**Ayvaz Russia
Moscow/Russia**
Tel: +74959951728
ayvazrus@ayvaz.com

**Ayvaz Germany
Viernheim/Germany**
Tel: +49 62046014399
germany@ayvaz.com

**Ayvaz Ukraine
Kiev/Ukraine**
Tel: +380 44 390 57 57
info@ayvaz.com.ua

**Tricorr
Warsaw/Poland**
Tel: +48-32-783-295-1
tricorr@tricorr.eu

**Haci Ayvaz M.E.
Dubai/U.A.E**
Tel: +971 563550822
+971 501306871
mideast@ayvaz.com

**Ayvaz China
Cixi City/China**
Tel: +86 0574 5897 3851
info@ayvazchina.com

**Ayvaz Kazakhstan LLP
Almaty/Kazakhstan**
Tel: +7 (727) 327 97 57
info_kz@ayvaz.com
www.ayvaz.kz

**Ayvaz N
Isperih/Bulgaria**
Tel: +359 8431 27 32
office@ayvaz-n.eu

**Ayvaz Serbia
Belgrad/Serbia**
Tel: +381 61 658 70 52
yakbiyik@ayvaz.com