

Firmware Package Version and Date	Change
1.08.01, 01/09	<ul style="list-style-type: none"> • Changed time dial range of 51 element fixed time curve from 0-30 s to 0-7,200 s. • Added Phase Toggle Delay setting for front panel HMI. • Added Off Mode Cooldown feature. • Added 51-3 element. • Added Var/PF control. • Added LSM Input settings. • Added Checksum Fail and CEM Hardware Mismatch pre-alarms. • Added kVar A, B, C, and Total metering. • Added several MTU items to metering. • Re-arranged <i>CANbus Setup</i> screens and added <i>ECU Setup</i> screens on front panel HMI. • Added support for CEM-2020H.
1.07.02, 09/08	<ul style="list-style-type: none"> • Finalized settings for AEM-2020.
1.06.00, 07/08	<ul style="list-style-type: none"> • Added settings for AEM-2020. • Added settings for Automatic Generator Detection. • Added settings for Integrating Reset on 51 function. • Added settings for Configurable Protection.
1.05.00, 04/08	<ul style="list-style-type: none"> • Added settings for CEM-2020.
1.04.00, 12/07	<ul style="list-style-type: none"> • Added settings for LSM-2020.
1.03.00, 08/07	<ul style="list-style-type: none"> • Added 32 and 40Q protection functions. • Added Automatic Restart function and Exercise Timer. • Added dual settings for 51, 27, and 59 functions. • Added Oil Pressure Crank Disconnect Enable. • Modified Prestart operation during rest cycle. • Added 2 additional Engine kW Overload Pre-Alarms. • Added Low Line Scale Factor for EPS Supplying Load and Engine kW Overload Pre-Alarms. • Changed the metering range of coolant temperature to 32-410 F. • Changed the Low-Coolant Temp Pre-Alarm range to 32-150 F.
1.02.00, 05/07	<ul style="list-style-type: none"> • Added Spanish language support.
1.00.08, 03/07	<ul style="list-style-type: none"> • Minor firmware improvements.
1.00.07, 01/07	<ul style="list-style-type: none"> • Added Chinese language support.
1.00.06, 11/06	<ul style="list-style-type: none"> • Initial release