



# Original Line® 3-Position

**Your configured part number: 020.011/0.011-D**

**Additional accessories: (NO ACCESSORIES)**

## Features and Benefits

### • **Maintenance Free Performance:**

- Lubed for life w/proprietary synthetic blend grease
- Blue and Improved design doubles previous cylinder life

### • **3-Position Model Types:**

- 3 positive stroke positions with a single cylinder
- Magnet option for position sensing applications
- Non-rotating rod option available

### • **Added Strength:**

- Piston to rod connection is threaded, sealed, and riveted securely in place
- Roll formed rod threads on both ends
- Aluminum alloy piston with blow-by flats

### • **Low Breakaway:**

- Inflatable, wear compensating, U-cup rod and piston seals
- Breakaway slots on each end cap for fast seal inflation

## Engineering Specifications

**Pressure Rating:** 250 PSI

### **Temperature Range:**

Buna N seals: -20° F (29° C) to 200° F (90° C)

Fluoroelastomer seals for high temperatures (up to 400° F) available

Magnetic piston option: max. operating temp. is 185° F

### **Materials:**

Rod: 303 stainless steel

Body: 304 stainless steel

End Caps: 6061 aluminum (RoHS compliant)

Rod and Pivot Bushings: Sintered bronze

## Service and Design Capabilities

### • **Catalog models available in 4 days or less**



### • **Custom design capabilities for your needs**

### • **Common modifications include:**

- Custom rod threads/lengths
- Customer logo/part# on cylinder body
- Additional standard port sizes/locations
- Special lubricants (FDA approved, etc.)
- Anodized or nickel plated end caps
- Clean room design with Krytox lubrication
- Special spring forces

**Leaders in Actuation.**

Bimba Manufacturing Company  
Monee, IL 60449-0068  
Telephone: 708.534.8544  
Toll Free: 800-44-BIMBA  
Email: [cs@bimba.com](mailto:cs@bimba.com)  
[www.bimba.com](http://www.bimba.com)



Powered by CADENAS PARTsolutions