



Your configured part number: **MF-250X0.50-DA-RB**

Features and Benefits

- **Mini Cylinders Mount Anywhere:**
 - Ideal for applications where space is limited
 - Single or double acting models available
- **Stroke Length Availability:**
 - 1/4" and 1/2" standard stroke lengths
 - Fractional stroke lengths available by adding a spacer
 - Contact Mead for custom stroke length
- **Clean and Compact Construction:**
 - MF series features flat mount style
 - MA series features threaded cylinder body for easy position adjustment

Engineering Specifications

Pressure Rating: 125 PSI Air

Temperature Range:

Buna N Seals: 0° F (-18° C) to 220° F (104° C)

Viton Seals: 0° F (-18° C) to 400° F (204° C)

Lubrication: Recommended - non-detergent petroleum based

Filtration: 40µ

Materials:

Rod: Stainless Steel

Rod Bushings: 660 Bronze

Service and Design Capabilities

- Experienced application engineers are available to provide complete pneumatic circuit solutions
- A full line of products including air preparation, valves, actuators, and specialty components are available
- Fast shipping and helpful customer service
- Custom design capabilities to meet your needs
- Call (877) MEAD-USA (877-632-3872)

Bimba Manufacturing Company

Monee, IL 60449-0068


Telephone: 708.534.8544

Toll Free: 800-44-BIMBA

Email: cs@bimba.com

www.bimba.com

Leaders in Actuation.



MF-250X0.50-DA-RB

THIS DRAWING CONTAINS PROPRIETARY DESIGNS AND/OR INFORMATION OF BIMBA MFG. CO. OR ITS SUBSIDIARIES AND IS NOT TO BE TRANSMITTED, REPRODUCED, USED OR DISCLOSED WITHOUT WRITTEN PERMISSION OF BIMBA MFG. CO. OR ITS SUBSIDIARIES. DESIGN REFLECTS OUR BEST ENGINEERING OPINION BASED ON WRITTEN APPLICATION SPECIFICATIONS RECEIVED. SUITABILITY OF A DESIGN FOR AN APPLICATION REQUIRES ANALYSIS AND/OR TESTS IN YOUR SPECIFIC SYSTEM.

Bimba is part of
IMI Precision
Engineering



Bimba Manufacturing Co.

Monee, IL. 60449
(800) 442-4622 www.bimba.com

PROPRIETARY DRAWING - Reference Only