



Centrifuge CENTRIC 200R

- Quiet operation, Maintenance Free Motor (Brushless motor)
- Double Lid Lock System
- Fast Cool Function
- Big LED Display
- 10 Preset programs

Rotors	Angle: 12 x 10 ml, 16 x 5 ml, 24 x 2,0 ml, 30 x 2,0 ml, Hematokrit rotor, PCR strip
Time	0 – 99 min, Hold function
Speed	500 – 16.200 RPM
Maks. RCF	25.000 x g
Temp. range	-9 °C to +40 °C
Programs	10
Noise	62 dBA
Dimensions / weight	282 x 360 x 665 mm / 50 kg



Centrifuge CENTRIC 400R

- Quiet operation, Maintenance Free Motor (Brushless motor)
- High RCF
- Double Motor Driven Lid Lock System
- Fast Cool Function
- Big LED display
- Robust design

Rotors	Swing out: 4 x 200 ml, 4 x 100 ml, 2 x 3 96 Well-plates Angle: 30 x 15 ml, 6 x 50 ml, 24 x 2,0 ml, 30 x 2,0 ml
Time	0 – 99 min, Hold function
Speed	500 – 18.000 RPM
Maks. RCF	30.000 x g
Temp. range	-9 °C to +40 °C
Programs	10
Noise	62 dBA
Dimensions / weight	350 x 650 x 545 mm / 79 kg

Centrifuge for Cytology and Immunology applications

- Centrifuge for cytology, urology, microbiology and virology
- Application for Immunology KIT preparation
- Wide range of accessories for different applications

MODEL	CENTRIC 150	CENTRIC 322	CENTRIC 250	CENTRIC 350	
Use	CITO	CITO	CITO	CITO	IMUNO
No. Places	4 or 8	12	8	12	26
Speed [RPM]	2000	2000	2000	2000	2000
Motor inductive	no	no	yes	yes	yes

PRP centrifuges

- Used for orthopedie, plastic surgery, veterianry
- Wide range of accessories

MODEL	CENTRIC 322A	CENTRIC 250	CENTRIC 350
Volume [ml]	10, 20, 60	10	10, 20, 60
No. Places	4	4	4
Speed [RPM]	2000	2000	2000
Motor inductive	no	do	yes



DOMEL



DOMEL, d.o.o.

Otoki 21, SI-4228 Železniki, Slovenia

BU LABORATORY SYSTEMS

Na Plavžu 79, SI-4228 Železniki, Slovenia

Tel.: +386 4 511 75 00

Fax: +386 4 511 75 01

E-mail: info.labs@domel.com

Website: <http://labs.domel.com>

Sales Manager

+386 4 511 75 10

Area Sales Manager SLO, CRO, BiH, SRB, MNE, MK

+386 4 511 75 12

Area Sales Manager EU & USA

+386 4 511 75 11

Area Sales Manager Middle East & Asia

+386 4 511 75 50



All our centrifuges have EC declaration of conformity. Their controlled lid, rotor recognition, speed limitation, and imbalance detection ensure safe operation. Handling is user friendly due to adjustable acceleration and deceleration as well as displaying of rotational speed and centrifuge force. Robustness of centrifuges and a long lifetime is ensured by metal housing, stainless steel rotor mount and metal rotors.

Centrifuge CENTRIC 150

- Low Maintenance Costs
- Simple and Easy Maintenance
- Aluminum rotors
- Fast spin
- Big LED display
- Robust design

Rotors	8 x 15 ml, 12 x 12 ml, 24 x 2,0 ml, Hematocrit rotor
Time	0,1 – 60 min, Hold function
Speed	500 – 13.000 RPM
Maks. RCF	15.120 x g
Noise	68 dBA
Dimensions / weight	275 x 330 x 240 mm / 14,5 kg



Centrifuge CENTRIC 250

- Quiet operation, Maintenance Free Motor (Brushless motor)
- Double Lid Lock System
- Fast spin
- Special features (Auto start, Lid opening, Beeper, 100 Programs)
- Big LED display

Rotors	Swing out: 6 x 12 ml, Angle: 8 x 15 ml, 12 x 12 ml, 24 x 2,0 ml, 30 x 2,0 ml, Hematocrit rotor, PCR strip rotor, Cyto rotor, PrP rotor
Time	0 – 99 min, Hold function
Speed	200 – 16.200 RPM
Maks. RCF	25.000 x g
Programs	100
Noise	62 dBA
Dimensions / weight	250 x 300 x 415 mm / 18 kg



Centrifuge CENTRIC 322A

- Low Maintenance Costs
- Simple maintenance
- Easy operation
- Quick Program Selection
- Robust Design

Rotors	Swing out: 4 x 100 ml, 2 x 3 96-Well Plates Angle: 30 x 15 ml, 6 x 50 ml, 24 x 2,0 ml
Time	1 – 99 min, Hold function
Speed	500 – 6.000 RPM
Maks. RCF	3.300 x g
Programs	15
Noise	68 dBA
Dimensions / weight	360 x 400 x 460 mm / 28 kg



Centrifuge CENTRIC 350

- Quiet operation, Maintenance Free Motor (Brushless motor)
- High RCF
- Small Footprint for High Sample Volume
- Double Lid Lock System
- Fast Spin Function
- Special features (Auto start, Lid opening, Beeper, 100 Programs)
- Big LED display

Rotors	Swing out: 4 x 200 ml, 2 x 3 96-Well Plates Angle: 30 x 15 ml, 6 x 50 ml, 24 x 2,0 ml, 30 x 2,0 ml, Hematocrit rotor, PCR strip rotor, Cyto rotor, PrP rotor
Time	0 – 99 min, Hold function
Speed	200 – 15.000 RPM
Maks. RCF	21.630 x g
Programs	100
Noise	62 dBA
Dimensions / weight	325 x 405 x 500 mm / 32 kg



Analogue Mini incubator

- Small Analogue Benchtop Incubator
- Big Transparent or Opaque Door

Volume	10 l or 23 l
Temp. range	Ambient temp. +5 °C up to +70 °C
Temp. accuracy	±0,5 °C pri 37 °C
Shelves	2 positions for 10 l 3 positions for 23 l
Dimensions / weight	10 l – 285 x 280 x 335 mm / 8 kg 23 l – 340 x 360 x 400 mm / 12 kg



Digital Mini incubator (not available in EU)

- Small Benchtop Incubator
- Big Transparent or Opaque Door
- Microprocessor control of temperature
- Temperature sensor PT-100

Volume	10 l and 23 l
Temp. range	Ambient temp. +5 °C up to +70 °C
Temp. accuracy	±0,5 °C at 37 °C
Dimensions / Weight	10 l – 285 x 280 x 335 mm / 8,3 kg 23 l – 340 x 360 x 400 mm / 12,8 kg
Shelves	2 positions for 10 l 3 positions for 23 l
Dimensions / Weight	10 l – 285 x 280 x 335 mm / 8,3 kg 23 l – 340 x 360 x 400 mm / 12,8 kg



Cooling incubator (not available in EU)

- Double Isolated Door
- Low Power Consumption
- Heating and Cooling with Peltier element
- Microprocessor control of temperature
- Temperature sensor PT-100

Volume	23 l
Temp. range	10 °C below Ambient temp. to 70 °C
Temp. accuracy	±0,5 °C at 37 °C
Shelves	3 positions
Dimensions / Weight	380 x 470 x 450 mm / 19 kg



Digital Water Bath

- Stainless Steel Chamber and Gabled Cover
- Big LED Display
- Microprocessor control of temperature

Volume	6 l and 12 l
Temp. range	Ambient temp. +5 °C up to 100 °C
Temp. accuracy	±0,5 °C at 37 °C
Container Dimensions	6 l – 320 x 170 x 180 mm 12 l – 300 x 240 x 200 mm / 12 kg
Dimensions / Weight	6 l – 380 x 290 x 230 mm / 8,6 kg 12 l – 380 x 370 x 280 mm / 12 kg