

**Intelligent Positioner (Intrinsically Safe)**

**Base Model:** SRD991-BHFS7EA4NY-V1 1

**FtJNCttoN:** iitelligeni Positioner SR.0991 certified Ex ia/  
Intrinsically Safe or not with advanced diagnostics to operate  
SRD991 pneumatic valve actuators. Input Signal 4-20 mA / HART /  
PROFIBUS-PA / FOUNDATION Fieldbus H1 according to  
FISeO

**B VERSION:** Single Acting

**H INPUT/COMMUNICATION:**

HART communication (4-20

mA)

**F ADDITIONAL INPUTS/OUTPUTS:** Position Feedback 4-20  
mA and one Binary Output

**S BUILT-IN LIMIT SWITCH:** Without

**7 CABLE ENTRY:** M20 x 1.5 with one plastic Cable Gland

**EA4 ELECTRICAL CERTIFICATION:** n 2 G Ex iane T4 Gb  
according to ATEX / JEeEx

**N ATTACHMENT KIT:** Order as auxiliary

**y MANIFOLD:** Pneumatic connection 1/4 - 18 NPT made of an  
additional manifold

**V11 OPTIONAL MODEL SUFFIX(ES) INCLUDED:** LCD  
w/Menu-Language in English / German / Russian