

HOUSINGS FOR SURFACE MOUNTING FOR BUILD IN OF DEVICES

**APG-1***

Art. no. 602826

Housing for surface mounting incl. seal GGD2448

Dimensions: 82 x 80 x 95 mm (W x H x D), without elbow-plug**Panelcut-out:** for 1 display at the format 48 x 24 mm**Connection:** elbow-plug according to EN 175301-803/A, 4-pin**Protection class:** IP65**Suitable for:** GIA 20 EB / GIR 230 ... / GIA 0420 / GIA 0420 SP / GIA 2448 /WE / GTH2448/1, 2, 3**APG-2***

Art. no. 603178

Housing for surface mounting incl. seal GGD2448

82 x 80 x 95 mm (W x H x D), without screw connections

for 1 display at the format 48 x 24 mm

2 x screw connections M12 x 1.5

IP65

APG-3*

Art. no. 603462

Housing for surface mounting incl. seal GGD2448

82 x 80 x 95 mm (W x H x D), without screw connections

for 2 displays at the format 48 x 24 mm

2 x screw connections M12 x 1.5

IP65

**APG-4***

Art. no. 602827

Housing for surface mounting incl. seal GGD4896

Dimensions: 125 x 75 x 126 mm (W x H x D), without screw connections**Panelcut-out:** for 1 display at the format 96 x 48 mm**Connection:** screw connections M12 x 1.5 and M16 x 1.5**Protection class:** IP65**Suitable for:** GIA 2000 / GIR 2000 PT / GIR 2002 ... / GTH 83 EG, / GTH 1150 EG**APG-6***

Art. no. 603179

Housing for surface mounting incl. seal GGD4896

125 x 175 x 126 mm (W x H x D), without screw connections

for 2 displays at the format 96 x 48 mm

screw connections 2 x M12 x 1.5 and 2 x M16 x 1.5

IP65

APG-7*

Art. no. 606825

Housing for surface mounting incl. seal GGD4896

122 x 72 x 126 mm (W x H x D), without screw connections

for 1 display at the format 72 x 36 mm

screw connections M12 x 1.5

IP65

GIR 300, GIR 360

* Note: All housings without installation device and without unit sticker! These (see page 124) have to be ordered separately!
The Installation device will be assembled for free in the housing (on common order) if desired.

SOLID STATE RELAYS

**WP66D10**

Art. no. 608519

Solid State Relays

WP66D25

Art. no. 608520

Solid State Relays

WP66D50

Art. no. 608521

Solid State Relays

WP66D75

Art. no. 608522

Solid State Relays

General:

The WP SSRs provide an economy option for users requiring devices to switch up to 75A.

- Panel mounting
- High thermal performance
- CE and UL / cUL
- RoSH compliant

Specifications:**Max. rated current:** 10, 25, 50, 75 A**Control voltage:** 48 ... 660 VAC**Load voltage:** 4 ... 32 VDC**Scope of supply:** Device

ALARM LIGHT WITH BUZZER



GIVES OPTICAL AND ACCOUSTIC ALARM

ALARM 230V

Art. no. 600913

Alarm light with buzzer

General:

Universal alarm device with flashlight and buzzer, which is connected easily to relay outputs and the 230 V grid.

Specifications:**Color:** red**Sound level:** 92 dB**Voltage supply:** 230 V AC / 50 Hz**Working temperature:** -20 ... +50 °C**Protection class:** IP 65**Suitable for:** e. g. GIR 2002, GIR 230, GIR 300