





Description	Value
General information:	
Product name:	NK 250-400/385 AA2F1AESBQQE2W3
Product No:	On request
EAN number:	On request
Technical:	
Pump speed on which pump data are based:	1490 rpm
Rated flow:	850.3 m³/h
Pump with motor (Yes/No):	Y
Rated head:	44.67 m
Actual impeller diameter:	385 mm
Nominal impeller diameter:	400
Primary shaft seal:	BQQE
Shaft diameter:	48 mm
Code for shaft seal:	BQQE
Mechanical seal type:	Single
Curve tolerance:	ISO9906:2012 3B
Pump version:	A2
Bearing design:	Standard
Materials:	
Type key, code for materials:	A
Type key, code for rubber components. E = EPDM, V=FKM:	E
Pump housing:	Cast iron EN-GJL-250 ASTM class 35
Wear ring:	Brass CuZn34Mn3Al2Fe1-C
Impeller:	Cast iron EN-GJL-200 ASTM class 30
Pump house, internal coating:	CED
Material code:	A
Code for rubber:	E
Shaft:	Stainless steel EN 1.4301 AISI 304
Installation:	
Maximum ambient temperature:	55 °C
Maximum operating pressure:	10 bar
Type key, code for pipework connection:	F
Pipe connection standard:	EN 1092-2
Type of inlet connection:	DIN
Type of outlet connection:	DIN
Size of inlet connection:	DN 300
Size of outlet connection:	DN 250
Pressure rating for connection:	PN 10
Coupling type:	Flexible w/spacer
Base frame design:	EN/ISO
Code for base frame:	10D
Grouting (Yes/No):	N
Connect code:	F
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-25 .. 120 °C
Selected liquid temperature:	20 °C



Pumped liquid = Water
Liquid temperature during operation = 20 °C
Density = 998.2 kg/m³





Company name:

Created by:

Phone:

Date:

12/01/2026

Description	Value
Density:	998.2 kg/m ³
Electrical data:	
Motor type:	INNOMOTICS
Rated power - P2:	132 kW
Mains frequency:	50 Hz
Rated voltage:	3 x 380-420D/660-725Y V
Rated current:	235 A
Starting current:	820 %
Cos phi - power factor:	0.85
Rated speed:	1490 rpm
IE efficiency:	IE4 96,4%
IE Efficiency class:	IE4
Motor efficiency at full load:	96.4 %
Motor efficiency at 3/4 load:	96.6 %
Motor efficiency at 1/2 load:	96.3 %
Number of poles:	4
Enclosure class (IEC 34-5):	IP55
Insulation class (IEC 85):	F
Built-in motor protection:	PTC
Motor No:	92910052
Bearing insulation type N-end:	N
Controls:	
Frequency converter:	None
Pressure sensor:	N
Others:	
Minimum efficiency index, MEI ≥:	0.46
Net weight:	1940 kg
Gross weight:	2040 kg
Shipping volume:	3.11 m ³
Language on pump nameplate:	GB

