



Company name:

Created by:

Phone:

Date:

19/01/2026

Description	Value
<b>General information:</b>	
Product name:	CUE 3X380-500V IP55 55KW
Product No:	On request
EAN number:	On request
<b>Technical:</b>	
Safety function:	None
RFI filter type EN 61800-3:	C1
Coating grade IEC721 3-3:	3C2
Approvals:	CE, CULUS, C-TICK
Cable gland entry:	Standard cable entry
<b>Installation:</b>	
Range of ambient temperature:	0 .. 50 °C
Relative humidity:	5-95 %
Mounted on:	WALL
Backplate (Yes/No):	N
CUE enclosure size:	C1
<b>Electrical data:</b>	
Rated power - P2:	55 kW
Mains frequency:	50 / 60 Hz
Rated voltage:	3 x 380-440/441-500 V
Rated current:	106-105 A
Maximum current consumption:	106 A
Efficiency at full load:	98 %
Enclosure class (IEC 34-5):	IP55
Mains input type:	Direct Connection
Built-in motor protection:	YES
Thermal protec:	external
Cable length:	150/300 m
<b>Others:</b>	
Net weight:	45 kg
Gross weight:	45.2 kg
Danish VVS No.:	382996550
Finnish LVI No.:	9414063
Country of origin:	DK
Custom tariff no.:	85044090

