




Description	Value
General information:	
Product name:	DDC 6-10 AR-PV/T/C-F-31I001FG
Product No:	On request
EAN number:	On request
Technical:	
Type key:	DDC 6-10 AR-PV/T/C-F-31I001FG
Max. Flow:	6 l/h
Max. flow in slow mode 50%:	3 l/h
Max. flow in slow mode 25%:	1.5 l/h
Min flow:	6.0 ml/h
Turn-down ratio:	1:1000
Approvals:	CE, CSA-US, NSF61, EAC, RCM
Valve type:	Standard
Maximum viscosity at 100 %:	50 mPas
Maximum viscosity in slow mode 50 %:	1800 mPas
Maximum viscosity in slow mode 25 %:	2500 mPas
Accuracy of repeatability:	1 %
Materials:	
Dosing head:	PVDF (Polyvinylidene fluoride)
Valve ball:	Ceramic
Gasket:	PTFE
Installation:	
Range of ambient temperature:	0 .. 45 °C
Maximum operating pressure:	10 bar
Installation set (Yes/No):	YES
Installation type:	4/6 mm up to 7,5 l/h, 16 bar
Pump inlet:	Hose 4/6 mm 3
Pump outlet:	Hose 4/6 mm 3
Max. Suction lift during operation:	6 m
Max. Suction lift during priming:	2 m
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 45 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Maximum power input - P1:	22 W
Mains frequency:	50 / 60 Hz
Rated voltage:	1 x 100-240 V
Enclosure class (IEC 34-5):	IP65 / TYPE 4X
Length of cable:	1.5 m
Type of cable plug:	EU
Inrush current:	25A at 230V for 2ms
Controls:	
Control variant:	AR
Control panel:	Front-Mounted
Level control:	YES
Analog input:	0/4-20 MA
Pulse control:	YES
Ext. Stop input:	Yes
Output relays:	2
Others:	





Company name:

Created by:

Phone:

Date:

12/01/2026

Description	Value
Net weight:	2 kg
Gross weight:	3 kg
Colour:	RED
Country of origin:	FR
Custom tariff no.:	84135040

