

Description	Value
General information:	
Product name:	DMX 132-10 B-SS/T/SS-X-E1A1A1
Product No:	On request
EAN number:	On request
Technical:	
Nominal flow rate at 50 Hz:	132 l/h
Number of dosing heads:	1
Approvals:	CE
Non return valve type, inlet pump 1:	Not spring-loaded
Max viscosity:	400 mPas
Materials:	
Dosing head, pump 1:	Stainless steel, 1.4571
Valve ball inlet:	AISI 316L
Valve gasket inlet:	PTFE
Installation:	
Max operating pressure at 50 Hz:	10 bar
Type of inlet connection:	Rp
Type of outlet connection:	Rp
Size of inlet connection:	3/4 inch
Size of outlet connection:	3/4 inch
Max. Suction lift during operation:	3 m
Liquid:	
Pumped liquid:	Water
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Power input P1:	0,370 kW kW
Mains frequency:	50 Hz
Max. frequency:	50 Hz
Rated voltage:	3 x 230/400 V, 50/60 Hz 440/480 V, 60 Hz V
Enclosure class (IEC 34-5):	IP 65/F
Power plug:	No plug
Mains cable:	No cable m
Controls:	
Control variant:	B
Stroke control:	Manual
Control panel:	No control panel (without AR control)
Level control:	Not integrated
Analog input:	Not integrated
Pulse control:	No
Ext. Stop input:	Not integrated
Analog output:	Not integrated
Pulse control:	Not integrated
Other in/output:	Not integrated
Output relays:	Not integrated
Frequency converter:	Not prepared for VFD
Others:	
Flow rate adjustment:	Manual
Diaphragm Leakage Detection:	NO
Grundfos Alldos PN:	226-132L-10087



