





Company name:

Created by:

Phone:

Date: 16/01/2026

Description	Value
General information:	
Product name:	DMX 460-6 B-PVC/E/C-X-E1U3U3XEMAG
Product No:	On request
EAN number:	On request
Technical:	
Nominal flow rate at 50 Hz:	460 l/h
Number of dosing heads:	1
Approvals:	CE,EAC,CNROHSEX
Non return valve type, inlet pump 1:	Standard
Non return valve type, outlet pump 1:	Standard
Max viscosity:	50 mPas
Materials:	
Pump housing:	Aluminium
Dosing head, pump 1:	Plastic
	PVC
Valve ball:	Ceramic
Valve ball:	Al2O3
Valve seat:	Composite
Valve seat:	PTFE
Valve gasket:	EPDM
Valve gasket:	Rubber
Installation:	
Max operating pressure at 50 Hz:	6 bar
Maximum permissible inlet pressure:	0 bar
Type of inlet connection:	Connection pack
Type of outlet connection:	Connection pack
Size of inlet connection:	19/27, 20/25
Size of outlet connection:	19/27, 20/25
Max. Suction lift during operation:	2 m
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 40 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Power input P1:	0.4 kW
Mains frequency:	50 Hz
Max. frequency:	50 Hz
Rated voltage:	3 x 230/400 V
Enclosure class (IEC 34-5):	IP65
Cable included (Yes/No):	N
Power plug:	No plug
Controls:	
Type of connector:	No plug
Type of control variant:	Standard
Frequency converter:	Not prepared for VFD
Others:	
Net weight:	19 kg
Gross weight:	30.3 kg
Shipping volume:	0.156 m³
Diaphragm Leakage Detection:	N





Company name:

Created by:

Phone:

Date:

16/01/2026

Order Data:

Position	Your pos.	Product name	Amount	Product No	Total
		DMX 460-6 B-PVC/E/C-X-E1U3U3XEMAG	1	On request	