


Data Sheet

Itemnumber....: 3240901159



A = 140	AC = 175	BB = 155	DB = M8	EG = 24	GD = 7	HD = 222	LB = 312
AA = 35	AD = 132	C = 56	E = 50	F = 8	H = 90	K = 12	TB = 100
AB = 177	B = 125	D = 24	EB = 40	G = 20	HA = 13	L = 362	TL = 100

Version

Type..... HMA2 90L-4
 Design..... Induction motor
 Standard series..... IEC 60034
 Phase / Voltage range..... 3~ / Low

Electrical design

Efficiency.....	IE2
Pole.....	4
Power at 50 Hz (kw).....	1,50
Hz.....	60 (60 Hz output)
Voltage.....	440VD
Winding voltage.....	400VD/690VY 50 Hz
Power output (kw).....	1,74
Duty.....	S1
Insulation class.....	F
Temperature rise.....	B

Mechanical design

Frame size.....	90
Mounting.....	B3
Rain cap.....	No
Protection class.....	IP55
Cooling method.....	IC411/TEFC
External grounding.....	Yes
Drain hole.....	Yes
Frame material.....	Aluminium
Material approval.....	None
Shaft.....	IEC standard
Key.....	Closed key
Balancing.....	Half key balancing
Vibration class.....	Grade-A
Weight (kg).....	18,0

Environment condition

Ambient temp. min. (°C)... -20
Ambient temp. max. (°C)... 45
Altitude (mtr up to)..... 1000

Bearing

Bearing
DE Bearing.....: 6205-ZZ/C3
NDE Bearing.....: 6205-ZZ/C3
Fixed bearing.....: DE

Terminal box

Terminal box	
Tbox position.....	Top
Cable entry direction.....	Right (from DE)
Cable entry	
Main.....	1 x M20x1,5 Ø8-13mm metal
Accessory.....	1 x M20x1,5 Metal blindcap
Terminal board thread.....	6-M4

Test values

```

Rotor inertia (kgm2)..... 0,0041
Noise level (dB(A))..... 58
No load current (A)..... 1,70
Winding resist. (ohm)..... 7,93
Starting time (sec.)..... 0,00
Temp. rise winding (K)..... 67
Temp. rise surface (K)..... 59

```

Motor protection

```

Thermal protection main....: PTC 3x 155 dgr
Thermal protection second..: None
Space heater.....: None
Temperature detector.....: No
SPM.....: No
IR wire.....: No
Tropical insulation.....: Yes

```

Explosion protection

According to.....: None

General

Direction of rotation.....: CW
Painting.....: RAL 9005
Nameplate.....: Multivoltage + VFD
Special packing.....: No
Special requirements.....: No

Rated power (kW)	1,50	1,46	1,80	1,74
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	3,25 1,88	3,35 1,94	3,25 1,88	3,35
Speed (rpm)	1440	1440	1730	1730
Power factor cos(phi)	0,81	0,82	0,81	0,81
Efficiency, 100/75/50 (%) . .	82,9/83,8/82,8	82,9/83,8/82,8	82,9/83,8/82,8	81,7/82,7/81,6
Ist/In	7,95	7,00	7,95	7,35
Full load torque (Nm)	9,95	9,65	9,95	9,65
Tst/Tn	2,50	2,32	2,50	2,16
Tmax/Tn	3,10	2,90	3,10	2,70
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45