


Data Sheet

Itemnumber..... 3240901459



A = 140	AC = 175	BB = 155	DB = M8	EG = 24	GD = 7	HD = 222	LA = 10	N = 130	T = 3,50
AA = 35	AD = 132	C = 56	E = 50	F = 8	H = 90	K = 12	LB = 312	P = 200	TB = 100
AB = 177	B = 125	D = 24	EB = 40	G = 20	HA = 13	L = 362	M = 165	S = 4-Ø12	TL = 100

Version

Type..... HMA2 90L-4
Design..... Induction motor
Standard series..... IEC 60034
Phase / Voltage range..... 3~ / Low

Electrical design

Efficiency..... IE2
Pole..... 4
Power at 50 Hz (kW)..... 1,50
Hz..... 60 (60 Hz output)
Voltage..... 440VD 60 Hz
Winding voltage..... 400VD/690VY 50 Hz
Power output (kW)..... 1,74
Duty..... S1
Insulation class..... F
Temperature rise..... B

Mechanical design

Frame size..... 90
Mounting..... B35
Rain cap..... No
Protection class..... IP55
Cooling method..... IC411/TEFC
External grounding..... Yes
Drain hole..... Yes
Frame material..... Aluminium
Material approval..... None
Shaft..... IEC Standard
Key..... Closed key
Balancing..... Half key balancing
Vibration class..... Grade-A

Environment condition

Ambient temp. min. (°C).... -20
Ambient temp. max. (°C).... 45
Altitude (mtr up to)..... 1000

Bearing

DE Bearing..... 6205-ZZ/C3
NDE Bearing..... 6205-ZZ/C3
Fixed bearing..... DE

Terminal box

Tbox position..... Top
Cable entry direction..... Right (from DE)
Cable entry
Main..... 1 x M20x1,5
Ø8-13mm metal
Accessory..... 1 x M20x1,5
Metal blindcap
Connection type..... Delta (D)
Terminal board thread..... 6-M4

Test values

Rotor inertia (kgm²)..... 0,0041
Noise level (dB(A))..... 58
No load current (A)..... 1,70
Winding resist. (ohm)..... 7,93
Starting time (sec.)..... 0,00
Temp. rise winding (K)..... 67
Temp. rise surface (K)..... 59

Motor protection

Thermal protection main..... PTC 3x 155 dgr
Thermal protection second.. None
Space heater..... None
Temperature detector..... No
SPM..... No
IR wire..... No
Tropical insulation..... Yes

Explosion protection

According to..... None

General

Direction of rotation..... CW
Painting..... RAL 9005 Gloss 10
Nameplate..... Multivoltage + VFD
Special packing..... No
Special requirements..... No

Rated power (kW)	1,50	1,46	1,80	1,74
Frequency (Hz)	50	50	60	60
Voltage (V)	400 690	380 660	480 830	440
Connection	D Y	D Y	D Y	D
Full load current (A)	3,25 1,88	3,35 1,94	3,25 1,88	3,35
Speed (rpm)	1440	1440	1730	1730
Power factor cos(phi)	0,81	0,82	0,81	0,81
Efficiency, 100/75/50 (%)	82,9/83,8/82,8	82,9/83,8/82,8	82,9/83,8/82,8	81,7/82,7/81,6
Ist/In	7,95	7,00	7,95	7,35
Full load torque (Nm)	9,95	9,65	9,95	9,65
Tst/Tn	2,50	2,32	2,50	2,16
Tmax/Tn	3,10	2,90	3,10	2,70
Duty	S1	S1	S1	S1
Ambient temp. (°C)	40	45	40	45