



PF 150

Reciprocating Horizontal
Triplex Plunger Pumps



- Compact dimension
- Splash lubrication and oil level switch
- Easy maintenance
- Low maintenance costs
- Internal reduction gear
- Self-adjusting seal packing
- Available with carbon steel or stainless steel hydraulic head

- Valve lifter controlled by means of pneumatic solenoid
- Regulating pressure valve
- Unloading valve
- Pressure-relief valve
- HP check valve
- Suction and/or delivery gauge
- Low and high pressure switches
- Lubrication system with oil filtration circuit + heat exchanger
- Simplex or duplex suction filter
- Manifold groups for suction/delivery


- Descaling system
- Disk saw cooling
- Hydrostatic bearing lubrication
- Press drive
- Hydraulic testing
- Coal mining
- Industrial cleaning
- Spunlace
- Deburring

see tables on the next page >>>

PF	150					
RATIO	Ø PLUNGER	HYDRAULIC HEAD MATERIAL		LUBRICATION		
E	30	S	Carbon steel	1	Splash	
L	35	D	Standard Stainless steel	3A	Assisted + water heat exchanger	
V	40	X	HR Stainless steel	3B	Assisted + air heat exchanger	
Z	45					
	50					
	55 (§)					
	60 (§)					
		HYDRAULIC HEAD VERSION				
		T35	NP 320 bar max.			
		T36	NP 320 bar max. + Valve lifter			
		T42	NP 420 bar max.			
		T43	NP 420 bar max. + Valve lifter			
		T55	NP 500 bar max.			
		T56	NP 500 bar max. + Valve lifter			


§ Available only with T35-T36 hydraulic head

Dimensions are referred to hydraulic head T35
Weight: kg 630




Selection Diagram

PF 150 - 50 Hz 4 POLES ELECTRIC MOTOR (1500 RPF) - MAX ABSORBED POWER 90 kW



PF 150 - 60 Hz 4 POLES ELECTRIC MOTOR (1800 RPF) - MAX ABSORBED POWER 90 kW



Also covered by smaller pump models T35/T36 Hydraulic head T42/T43 Hydraulic head T55/T56 Hydraulic head

1 MPa = 10 bar. The pump performances are referred to a volumetric efficiency of 100% and a mechanical efficiency of 89%, with water at 20°C. Input speed range 900-1800 r.p.m. For performances and uses other than the ones listed in this catalogue, please contact INOXIHP technical office for assistance.

Pumping Group

PF 150





Composed of

- Pump PF 150 with splash or assisted lubrication complete with delivery pressure gauge and flanges
- Electric motor
- Safety valve
- Coupling with cover
- Frame
- Suction pressure switch

Options

- Manifold groups for suction/delivery
- Junction box
- Suction filters simplex or duplex with/without clogging detection sensor
- Valve lifter controlled by means of pneumatic solenoid
- HP check valve
- Low and high pressure switches
- Simplex or duplex suction filter

Dimensions



POWER (kW)	DIMENSIONS (mm)			WEIGHT (Kg)
	A	B	C	
37	1655	936	1150	1125
45	1685	936	1150	1160
55	1750	936	1150	1230
75	1845	971	1150	1420
90	1875	971	1150	1550



These pump and pumping group model are EAC certified



INOXHIP S.r.l.

IT - 20834 Nova Milanese (MB) - Via Garibaldi, 89 - Tel: +39 0362 190111

Fax: +39 0362 1901008 - E-mail: inoxhip@inoxhip.com - inoxhip.com

INOXHIP
ABOUT USING WATER