



JB 116

Junction Box

FEATURES

- From the Vibro-Meter® product line
- Die-cast polyester enclosure
- Fully insulated and corrosion resistant
- Protection against mechanical damage, water and dust: IP65 protection rating
- ⚠ ➤ Certified for use in potentially explosive atmospheres only with Ex i certified products from Meggitt Sensing Systems' Vibro-Meter® product line



DESCRIPTION

The JB 116 junction box is suitable for connecting the integral cable of an accelerometer, for example, from the Vibro-Meter CA xxx or CE xxx series, and a signal transmission cable.

It is recommended to use a permanently installed junction box to make and protect the connection between a transducer and its extension cable, which goes to a remote monitoring rack.

The cables are fed into the junction box via stuffing glands. The cable ends are then screwed to terminal blocks, to easily create a permanent connection.

This polyester junction box is approved for use in explosive atmospheres (Ex) and offers protection against the possible splashing of oil, water or corrosive medium encountered in severe industrial environments (such as offshore or petrochemical applications).



Information contained in this document may be subject to Export Control Regulations of the European Union, USA or other countries. Each recipient of this document is responsible for ensuring that transfer or use of any information contained in this document complies with all relevant Export Control Regulations. ECN N/A.

SPECIFICATIONS

GENERAL

Material	: Polyester reinforced with glass fibre
Cover	: Sealed by neoprene gasket
Colour	: Black (RAL 9011) with blue plate (Ex approved)
Mounting	: M4 x 16 mm Allen head screws
Dimensions	: See the Mechanical drawing

INPUT / OUTPUT STUFFING GLANDS

Material	: Nickel-plated brass
Seal	: Viton®

ENVIRONMENTAL

Protection rating	: IP65 according to DIN 40050
Temperature range	: -40°C to +100°C
Impact resistance	: 4 mJ/mm ² (DIN 53453)
Surface resistivity	: < 10 ⁹ Ohm (DIN 53482)
Chemical resistance	: Good resistance to sea water, acids, alkaline solutions, solvents, gasoline and oils.
Flammability	: Self extinguishing, UL94V-0

Explosive atmospheres

Available in Ex approved versions for use in hazardous locations

Industrial housing

Type of protection Ex e: increased safety		
Europe	EC type examination certificate	II 2 G (Zones 1, 2) Ex e II


Surface resistivity for Ex version : < 10⁹ Ω (DIN 53482)

Stuffing glands

Type of protection Ex e: increased safety		
Europe	EC type examination certificate	II 2 G/D (Zones 1, 2) Ex e II

 For specific parameters of the mode of protection concerned and special conditions for safe use, please refer to the certificates that are available from Meggitt SA on demand.

MECHANICAL DRAWING



Note: all dimensions in mm unless otherwise stated.

ORDERING INFORMATION

Ordering Number: 823 - 116 - 000 - 012 - B1 - C1

INPUT CABLE FITTING (B)	
Cable gland M12 x 1.5 for cable Ø4 - Ø8 mm	03
Cable gland M16 x 1.5 for cable Ø6 - Ø11 mm	04
Adaptor M16 x 1.5/PG9	08

OUTPUT CABLE FITTING (C)	
Cable gland M12 x 1.5 for transducer cable Ø4 - Ø8 mm	03
Cable gland M16 x 1.5 for transducer cable Ø6 - Ø11 mm	04
Adaptor M16 x 1.5/PG9	08

Headquartered in the UK, Meggitt PLC is a global engineering group specializing in extreme environment components and smart sub-systems for aerospace, defence and energy markets.

Meggitt Sensing Systems is the operating division of Meggitt specializing in sensing and monitoring systems, which has operated through its antecedents since 1927 under the names of ECET, Endevco, Ferroperm Piezoceramics, Lodge Ignition, Sensorex, Vibro-Meter and Wilcoxon Research. Today, these operations are integrated under one strategic business unit called Meggitt Sensing Systems, headquartered in Switzerland and providing complete systems, using these renowned brands, from a single supply base.

The Meggitt Sensing Systems facility in Fribourg, Switzerland was formerly known as Vibro-Meter SA, but is now Meggitt SA. This site produces a wide range of vibration and dynamic pressure sensors capable of operation in extreme environments, leading-edge microwave sensors, electronics monitoring systems and innovative software for aerospace and land-based turbo-machinery.



All statements, technical information, drawings, performance rates and descriptions in this document, whilst stated in good faith, are issued for the sole purpose of giving an approximate indication of the products described in them, and are not binding on Meggitt SA unless expressly agreed in writing. Before acquiring this product, you must evaluate it and determine if it is suitable for your intended application. Unless otherwise expressly agreed in writing with Meggitt SA, you assume all risks and liability associated with its use. Any recommendations and advice given without charge, whilst given in good faith, are not binding on Meggitt SA.

Meggitt Sensing Systems takes no responsibility for any statements related to the product which are not contained in a current Meggitt Sensing Systems publication, nor for any statements contained in extracts, summaries, translations or any other documents not authored by Meggitt Sensing Systems. We reserve the right to alter any part of this publication without prior notice.

In this publication, a dot (.) is used as the decimal separator and thousands are separated by spaces. Example : 12345.67890.

Sales offices

Meggitt Sensing Systems has offices in more than 30 countries. For a complete list, please visit our website.

Your local agent

Head office

Meggitt SA
Route de Moncor 4
PO Box 1616
CH - 1701 Fribourg
Switzerland

Tel: +41 (0)26 407 11 11
Fax: +41 (0)26 407 13 01

www.meggittsensingssystems.com
www.vibro-meter.com

