



ADVANCED FLUID
MANAGEMENT SOLUTIONS

RAASM S.p.a.

Via Marangoni 33, 36022
S. Zeno di Cassola (VI) Italy
Tel. +39 0424 570891
info@raasm.com

P/N 33196

Pneumatic piston pump s. 650 for transferring oil and similar, R 1:1 - 40 l/min with Teflon® seals and suction tube 940 mm with bung adaptor for 180÷220 kg drums

AREAS OF USE

Aeronautics, Agriculture, Automotive, Building and road construction, Manufacturing industry, Mining industry, Lube trucks and transports, Railway transport

FEATURES

Flow rate	40 l/min
Ratio	1:1
Compatible fluids	oils, lubricants and similar
Suction tube upper body	aluminum
Suction tube	carbon steel
Air inlet connection	G 1/4" (f)
Fluid outlet connection	G 3/4" (f)
Air working pressure	6 ÷ 8 bar
Average air consumption	370 l/min
Noise level	81 dB
max deliverable oil viscosity	SAE 130
Bung adaptor	standard
Suitable for drums or tanks	suitable for drums 180 ÷ 220 kg
Packing	No. 1 - 0,020 m3
Weight	7,4 kg



OVERALL DIMENSIONS (mm)

