

Art. No. 153037



- Degree of protection IP66, suitable for Zones 1, 2, 21 and 22 world-wide, extreme temperature range of –45 ... +55 °C
- No impact of torsional forces from the cable on the seal
- Strong mechanical protection against damage through high-quality, glass fibre-reinforced plastics

WebCode 8579E



R. STAHL Series 8579/12 CES plugs for Zone 1/21 are 4- or 5-pole 63 A plugs. The floating pins allow them to be inserted and removed quickly and easily. The pivoting strain relief makes it easier to install the cable. Self-cleaning and corrosion-free plug pins made from high-quality materials ensure optimum electrical contact.


Technical Data

Explosion Protection	
Certificates	ATEX (PTB), Brazil (ULB), EAC (LPE), IECEx (PTB), Korea (KGS), Taiwan (ITRI)
Mechanical Data	
Type of protection note	according to IEC/EN 60529
Weight	0.88 kg
Components	
Cable diameter note	Ring 1 + 2 + 3: 24 ... 27 mm Ring 2 + 3: 27 ... 30 mm Ring 3: 30 ... 33 mm without inner ring: 33 ... 36 mm

Technical Drawings




Dimensional Drawings (All Dimensions in mm [inches]) – Subject to Alterations



A = 260 mm B = 84 mm C = 69.5 D = 112 mm

Art. No. 153037

Accessories and Spare Parts

Protective cap for plugs 63 A		Art. No.
	4-/5-poles	153261

We reserve the right to make alterations to the technical data, dimensions, weights, designs and products available without notice. The illustrations cannot be considered binding.