



TSURUMI PUMP

80UPZ 3-phase
50Hz

UPZ-series 80mm discharge,
wet-well and dry-well installation, hydraulically
highly efficient channel impeller and IE3 premium
efficiency motor, moisture sensor

Sewage pump equipped with a vortex-impeller
and a wide pump-casing. This construction
prevents clogging by big or fibrous
impurifications. The pumps are as a standard
equipped with a moisture sensor and a cooling
jacket and thus can constructively be installed
dry- and wet-well mounted. Option for
explosion-proof version available.





Vortex Impeller

This impeller is used mainly to avoid clogging or wear by large or stringy solids in the water. It accelerates part of the water to great speed, and this speed is used to smoothly move all the water from inlet to outlet.

Optional Accessories:

- duck-foot for guide rails:
 - guide support
 - duck foot
- Bend
- Stand set for free-standing version



Available options



- Explosion proof version
- Oil sensor
- Motor versions up to 2.9 kW in d.o.l., 3.7kW-motor either in d.o.l.- or star-delta-start, from 5 kW on only start-delta-start
- All pumps can be operated with soft-starter and frequency-converter





Specifications:

Model	free standing	with guide rail fitting	Colour code curve	Bore mm	Power output kW	Phases	r.p.m.	Head max. m	Capacity max. l/min	Starting method	Dry weight kg without cable		Impeller passage mm
											free standing	with guide rail fitting	
80UPZM42.9LLTOS80UPZM42.9L	1	80	2,9	3	1450	8,4	1005	direct	121,0	121,0	80		
80UPZM42.9L TOS80UPZM42.9L	2	80	2,9	3	1450	10,8	1333	direct	122,0	122,0	80		
80UPZM42.9 TOS80UPZM42.9	3	80	2,9	3	1450	12,8	1550	direct	122,0	122,0	80		
80UPZM43.7H TOS80UPZM43.7H	4	80	3,7	3	1450	14,7	1413	star/delta	122,0	122,0	80		
80UPZM45.0 TOS80UPZM45.0	5	80	5,0	3	1450	14,7	1967	star/delta	122,0	122,0	80		
80UPZM46.5 TOS80UPZM46.5	6	80	6,5	3	1450	17,2	2217	star/delta	139,0	139,0	80		


3.7 kW version available in d.o.l. or star-delta

o Discharge bore mm		80mm
Pumping Fluid	Type of Fluid	Municipal sewage
	Temperature	0-40°C
Pump	Components	Vortex impeller
	Impeller	Double mechanical seal
	Shaft Seal	Shielded ball bearings
	Bearings	
	Material	
	Impeller	Grey iron casting EN-GJL-250
	Casing	Grey iron casting EN-GJL-250
	Shaft Seal	SiC, upper in oil bath
	Wearing	Bronze
Motor	Motor Protector (built-in)	Miniature protector
	Insulation	Insulation class H
	Phase / Voltage	3-phase / 400V / 50Hz / d.o.l., 3-phase / 400V / 50Hz / s.d.
	Lubrication	Turbine oil (ISO VG32)
	Type, Poles	Induction motor, 4 poles, IP68
	Material	
	Casing	Grey iron casting EN-GJL-250
	Shaft	Stainless steel EN-X14Cr-Mo-S17
	Cable	Rubber, 10m H07RN8-F
Discharge Connection		Flange DIN/ANSI DN80 (PN10)
Optional Accessories		Guide rail fitting "TOS" (guide support, duck foot bend, lifting chain) / Bend and stand set for free standing types




Dimensions in mm:

Model	A	B	B1	C	C1	DN1	DN2	DN3	F1	F2	F3	G	H	J1
80UPZM42.9LLT22	375	220	310	155	80	100	3"	125	203	301	395	598	137	
80UPZM42.9L T22	408	250	316	158	80	100	3"	125	203	301	395	628	137	
80UPZM42.9 T22	408	250	316	158	80	100	3"	125	203	301	395	628	137	
80UPZM43.7H T22	408	250	316	158	80	100	3"	125	203	301	395	628	137	
80UPZM45.0 T22	408	250	316	158	80	100	3"	125	203	301	395	628	137	
80UPZM46.5 T22	792	408	250	316	158	80	100	3"	125	203	301	395	628	137



Dimensions - guide rail fitting type in mm:

Model	A	B	B1	C	C1	D	DN1	DN2	E
80UPZM42.9LL	722	375	220	310	155	742	80	100	112
80UPZM42.9L	722	408	250	316	158	775	80	100	112
80UPZM42.9	722	408	250	316	158	775	80	100	112
80UPZM43.7H	722	408	250	316	158	775	80	100	112
80UPZM45.0	722	408	250	316	158	775	80	100	112
80UPZM46.5	792	408	250	316	158	775	80	100	112



Tsurumi (Europe) GmbH

Wahlerstr. 10
D-40472 Düsseldorf
Tel.: +49 (0)211-4179373
Fax: +49 (0)211-417937-480
Email: sales@tsurumi.eu
www.tsurumi.eu

We reserve the right to change specifications and designs herein for improvement without prior notice. Our pumps are for professional use only. In the event that Tsurumi (Europe) GmbH have, in exceptional cases taken over, a manufacturer's warranty, this entitles the enduser to assert remedy free of charge against Tsurumi (Europe) GmbH due to any defect to the product occurring during the guarantee period (see below), also then when the warranty claims against the seller do not or no longer exist. In the event of malfunction, which is attributable to the improper handling by the enduser, no guarantee claim shall arise. Further claims shall not result from the warranty, unless if something to the contrary has explicitly been determined. The decision as to whether remedy is effected by way of replacement or repair shall be at the choice of Tsurumi (Europe) GmbH. The claims shall be time barred after a period of three months after expiry of the guarantee period, however, not before expiry of the warranty period which is valid towards the seller. In the event of doubt, the warranty period shall correspond with the warranty period which is valid between the end-user and his seller.

