

E7T CONTROL UNIT SEQUENCER 4÷16 OUTPUT CHANNELS



DESCRIPTION

Sequencer for controlling the pneumatic cleaning of industrial dust collector systems. It has 3 output relay contacts and 2 digital input contacts. Luminous LCD display, which allows to read the unit operating status, the active solenoid valves and any alarms, at all times.

OPTIONS UPON REQUEST

- Activation of 2 solenoid valves for every output channel.
- Cable glands for power supply input and output of solenoid valves drive cables.
- Connector from wired panel for connection to Matrix cabling.
- Zone 22 ATEX Certification.

REFERENCE STANDARDS

- Directive 2014/30/EC Electromagnetic Compatibility meeting European harmonised standards EN61000-6-2:2005 class B in standard EN61000-6-4:2001
- Directive 2014/35/EU Low Voltage meeting European harmonised standards EN 60947-1:2004

For additional information and technical specifications, consult www.turbocontrols.eu

TECHNICAL SPECIFICATIONS

Power supply voltage	115 Vac 50-60 Hz ± 10 % 230 Vac 50-60 Hz ± 10 %
Power supply voltage upon request	24 Vac ± 10 % 24 Vdc ± 10 %
Output voltage for solenoid valves for solenoid valves	115 Vac 50-60 Hz 230 Vac 50-60 Hz 24 Vac 24 Vdc
Inputs	Remote enabling consent switch. Post-cleaning cycles fan switch.
Solenoid valves output channels	01 ÷ 16
Electric consumption	28 Watts at maximum load
Alarm Relays	3 normally closed Maximum load: 3A @ 250Vac, 2A @ 24Vdc, 24 Vac.
Screen	Backlit monochromatic graphic LCD B/N 128 x 64 pixel
5 x 20 mm glass fuse	115 or 230 Vac 1 x 1 A 24 Vac or 24 Vdc 1 x 3 A
Operating temperature	-10 °C - 55 °C
Storage temperature	-20 °C - 60 °C
Environmental humidity	0 ÷ 95% Relative non condensing
Valves opening impulse time	50 m.sec. ÷ 10 sec.
Interval pause time between valves opening	1 sec. ÷ 7200 sec.
Casing	Base in ABS Lid in Polycarbonate
Protection rating from water and dust	IP65 DIN EN 60529
Shock resistance	IK07 2 Joule (EN62262)

